

# Mobile Gas Powered Compressors for Service Industry

Briggs & Stratton gas powered compressors designed for field work where an electrical power source is not available.

Medium duty, 2 stage air compressors designed for field service are equipped with 30 gallon ASME code horizontal tank with manual drain. Pressure preset at 145 PSI (load) and 175 PSI (unload). Each Briggs & Stratton OHV engine features cast iron cylinders, electric start, splash type lubrication and gas saving throttle control that meets CARB low emission requirements. (1) year limited parts and labor warranty.

## 8 HP Truck Mount

- 8 HP Briggs & Stratton Intek OHV engine
- Aluminum head and crankcase for fast heat dissipation
- Finned after-cooler and after-cooler provide low operating temperatures and high efficiency

## 10 HP Truck Mount

- 10 HP Briggs & Stratton Intek OHV engine
- Aluminum head and crankcase for fast heat dissipation
- Finned after-cooler and after-cooler provide low operating temperatures and high efficiency.

## 11 HP Truck Mount

- 11 HP Briggs & Stratton Vanguard OHV engine
- 2 cylinder pump with cast iron crankcase, cylinders and heads.
- Finned after-cooler and after-cooler provide low operating temperatures

## 16 HP Truck Mount

- 16 HP Briggs & Stratton Vanguard OHV engine
- Built for large volume CFM requirements (32 CFM at 175 PSI) and businesses that use high volume (CFM) air tools or sandblasting equipment out in the field.
- Cast iron compressor features four cylinders, taper roller bearings, finned intercoolers and concentric valves.



**GC6830B**



**GC61630B**

INDUSTRIAL Gates #	HP	Tank Gal.	Motor	Type	Disp. CFM	SCFM @175 PSI	L x W x H (inches)	Weight (lbs)	Pump Cyl	Pump RPM
GC6830B	8	30	Briggs & Stratton	Intek	19.5	13.5	40 x 19 x 39	300	2	1300
GC61030B	10	30	Briggs & Stratton	Intek	24.5	17.0	40 x 19 x 39	302	2	1065
GC61130B	11	30	Briggs & Stratton	Vanguard	22.0	16.0	43 x 18 x 39	430	2	800
GC61630B	16	30	Briggs & Stratton	Vanguard	41.0	32.0	50 x 24 x 43	550	4	800

